

Flexible. Specific. Innovative.

PA DUOPART®

... the burr-free connection solution!



Benefits:

- Burr-free surface thanks to non-welded tubing sections
- Ideally suited for push-in connectors
- Non-welded sections recur regularly
- Customized installation lengths are possible
- No complicated bundling per hand necessary
- Easier identification through different colored tubes
- High chemical resistance to oil, grease, fuels, solvent and hydraulic fluids
- Material is fully compliant with DIN 73378 and DIN 74324
- Lightweight
- Highly resistant to shock and impact
- Excellent compressive strength
- Highly resistant to stress cracking
- Excellent abrasion resistance characteristics
- Temperature range -40 °C to +85 °C

Welding parameters:

Welded	Non-welded section
approx. 60 mm	approx. 200 mm

Applications:

- Suitable for push-in connectors
- Pneumatic control line
- Automotive
- Vacuum

Material:

- Nylon

Standard color:

■ Blue

■ Black

- Customized welding parameters and special colours on request

The partially welded PA DUOPART® - the next generation of twin pneumatic tubing!

Novoplast Schlauchtechnik GmbH
In den Langen Stücken 6
38820 Halberstadt · Germany
Phone +49 3941 68 69-0
Fax +49 3941 68 69-189
www.schlauchtechnik.de
Industry.Novoplast@MasterflexGroup.com
A MASTERFLEX GROUP COMPANY

stand: 07/2017
photos: file Novoplast Schlauchtechnik GmbH

NOVOPLAST
SCHLAUCHTECHNIK

Connecting Values