

Flexible. Specific. Innovative.

XFlame soft®

... hold firm – even
when the sparks fly!



Advantages:

- Inflammable according to UL94 V0/V2
- Welding spray resistant
- Halogen-free according to EN 50267-2-1 (corresponds with IEC 60754-1)
- Self-extinguishing in case of fire
- LABS-free (free of substances that prevent paint adhesion)
- For use with drag chains
- Plasticizer-free
- Very good wear resistance
- Bend-resistant
- Highly elastic
- For temperature ranges from -40 °C to +90 °C
- Minimum burst pressure at 23°C: 34 bar (Values under Novoplast test conditions determined for tube size 6x2x10 mm)

Applications:

- Welding systems
- Welding robots
- Welding machines
- Spot welding tongs
- Associated welding areas

Standard color:

■ Black

- Dimensions and special colors on request

The elastic XFlame soft® is your partner for high flexibility applications.

Novoplast Schlauchtechnik GmbH
In den Langen Stücken 6
38820 Halberstadt · Germany
Phone +49 3941 68 69-0
Fax +49 3941 68 69-189
www.schlauchtechnik.de
Industry.Novoplast@MasterflexGroup.com

A MASTERFLEX GROUP COMPANY

stand: 05/0217 - photos: file Novoplast Schlauchtechnik GmbH - © www.fotolia.de

 **NOVOPLAST**
SCHLAUCHTECHNIK

Connecting Values